

CENTER 317

HUMIDITY TEMPERATURE METER (DEW POINT & WET BULB)



CE

Feature:

- Dew Point and Wet Bulb temperature Measurement.
- Fast response.
- Auto shut off for Battery Saving.
- MAX/MIN Function.
- Dual displays:
Primary display for Humidity;
Secondary displays for temperature.

CENTER®

CENTER 317 HUMIDITY TEMPERATURE METER

SPECIFICATIONS

Measurement Range:

Temperature: $-20^{\circ}\text{C} \sim 60^{\circ}\text{C}$; $-4^{\circ}\text{F} \sim 140^{\circ}\text{F}$

Humidity: 0%RH~100%RH

Resolution: 0.1°C/0.1°F/0.1%RH

Accuracy:

Temperature: $\pm 0.8^{\circ}\text{C}$, 1.6°F

Humidity: $\pm 2.5\% \text{RH}$

Sampling Rate: 2 times/sec

Humidity Sensor:

Electronic capacitance polymer film sensor.

Battery Type: 1.5V AA size battery x 4

Operating Condition: 0°C to 40°C (<80%RH)

Dimensions: 210×65×43mm

Accessories: Batteries, Instruction Manual



LED Back Light

1:1 Size

Dual Display



Primary display
for Humidity;
Secondary displays
for temperature.



Pull Up
Sensor
Protector.



33%RH / 75%RH
Humidity Standard (OPTIONAL)

* The specifications and other information in this catalogue are subject to change without prior notice.

Distributed by:

CENTER[®]
CENTER TECHNOLOGY CORP.

4/F., NO.415, Jung-Jeng Rd., 238 Shu-Lin, Taipei, Taiwan
TEL: 886-2-26763926 E-Mail: center@centertek.com
FAX: 886-2-26763925 http: //www.centertek.com